



HP Lubricants - Product Data Sheet



HP GEAR OIL XP 85W 140

- **HP GEAR OIL XP 85W 140 IS MULTIGRADE OIL CONTAINING EXTREME PRESSURE ADDITIVES FOR HEAVY DUTY SERVICE.**
- **MEETS API GL – 5, MIL – L 2105 C/D AND EP TYPE GL – 5 LEVEL OF IS : 1118 :1992 SPECIFICATIONS**
- **RECOMMENDED FOR HYPOID DIFFERENTIAL, REAR AXLE & FINAL DRIVES.**
 - **EXCELLENT THERMAL & CHEMICAL STABILITY**
 - **FUEL ECONOMY**
 - **GOOD PERFORMANCE EVEN UNDER VARYING LOADS**

KINEMATIC VISCOSITY, CST. @ 100 °C	26 – 32
VISCOSITY INDEX, MIN	90
FLASH POINT, (COC), °C, MIN	180
POUR POINT, °C, MAX	-12
CORROSION, COPPER STRIP, AT 121 °C FOR 3 HOURS , MAX	3
CHANNEL POINT DEG C	-20

**PRESS TO
RETURN** 

**FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE**