

ATLANTA MARINE D 3005

DESCRIPTION

ATLANTA MARINE D 3005 is designed for the crankcase lubrication of slow speed 2 stroke crosshead diesel engines.

APPLICATIONS

- Crankshaft lubrication
- Oil cooled pistons
- Shaft bearing lubrication

SPECIAL FEATURES

- Very good detergency level
- Very good thermal stability
- Excellent anti-rust and anti-corrosive properties
- High resistance to foaming

PHYSICO-CHEMICAL PROPERTIES

CHARACTERISTICS	UNITS	ATLANTA MARINE D 3005
S.A.E GRADE		30
Density at 15°C	Kg / m³	895
Kinematic viscosity at 40°C	mm² / s	105
Kinematic viscosity at 100°C	mm² / s	11.5
Pour Point	°C	-9
Flash Point (COC) ASTM D 92	°C	>220
BN (ex-TBN) ASTM D 2896	mgKOH / g	6

Characteristics of this chart are indicative typical values

APPROVALS

ATLANTA MARINE D 3005 is approved by MAN B&W, Wartsila and other major engine builders.

For details log on to: www.hindustanpetroleum.com | Email: lubescare@hpcl.in | Toll Free: 1800 120 4725 / 1800 121 4725 | Phone: +91 22 23030000 Follow us on : www.facebook.com/hplubricantsfromhindustanpetroleum