



# LUBRICANTS

POWER TO PERFORM

## TALUSIA UNIVERSAL

### DESCRIPTION

TALUSIA UNIVERSAL cylinder oil suitable for use in engines running both high and low sulphur fuels. Its patented formulation is specially designed for the cylinder lubrication of slow speed 2-stroke diesel engines when running with fuel having a large range in sulphur level.

### APPLICATIONS

Talusia Universal covers the special operational needs when using fuel with a sulphur level between 0.5% and 4.5%. With Talusia Universal no need to change to a special cylinder oil when entering in SECA.

### SPECIAL FEATURES

- Minimal piston ring and liner wear
- Maximum cleanliness
- Reduced engine maintenance costs
- Extended periods between overhauls

### PHYSICO-CHEMICAL PROPERTIES

CHARACTERISTICS	UNITS	TALUSIA UNIVERSAL
S.A.E GRADE		50
Density at 150C	Kg / m <sup>3</sup>	930
Kinematic viscosity at 100 <sup>o</sup>	mm <sup>2</sup> / s	19
Pour Point	<sup>o</sup> C	-9
Flash Point (COC) ASTM D 9	<sup>o</sup> C	>230
BN (ex-TBN) ASTM D 2896	mgKOH / g	57

Characteristics of this chart are indicative typical values

### APPROVALS

TALUSIA UNIVERSAL satisfies the requirements and recommendations of the engine manufacturers.