



HP Lubricants - Product Data Sheet



HP KOOLKUT 70

METAL WORKING FLUID CONTAINING NO OIL BUT CONSISTING OF SPECIAL CORROSION PREVENTIVE ADDITIVES IN WATER. THIS PRODUCT IS SUPPLIED AS CONCENTRATE

APPLICATION AREAS:

RUST PREVENTIVE TYPE OF COOLANT SPECIFICALLY DESIGNED FOR GRINDING AND HIGH SPEED MACHINING. RECOMMENDED DILUTION RATIO WITH WATER IS 2-4 PERCENT

PHYSICOCHEMICAL PROPERTIES:

PROPERTIES	KOOLKUT 70
COLOUR AFTER DILUTION	FLOUROSCENT GREENISH YELLOW
COPPER CORROSION@ 100deg C, 3HRS, MAX	1
pH OF 1:50 SOLUTION IN DISTILLED WATER MAX	9
CORROSION RATING 40:1 EMULSION IN DISTILLED WATER MAX	0

PERFORMANCE BENEFITS:

SUPERIOR COOLING PROPERTIES
EXCELLENT RUST PREVENTIVE PROPERTIES
LOW GRINDING WHEEL CLOGGING

CONT...

FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE