



HP Lubricants - Product Data Sheet



HP RACER 4

- MULTIPURPOSE ENGINE OIL FOR LUBRICATION OF ENGINE, GEAR BOX & WET CLUTCHES IN 4-STROKE TWO WHEELERS
- MEETS API SG AND JASO T903:MA SPECIFICATIONS (THE PRODUCT IS ON FILE WITH JALOS)
- RECOMMENDED FOR USE IN ALL 4 STROKE MOTORCYCLES, SCOOTERS, MOPEDS & SCOOTERETES
 - OPTIMISED CO-EFFICIENT OF FRICTION
 - EXCELLENT OXIDATION STABILITY
 - SLUDGE & VARNISH CONTROL
 - GEAR ANTIWEAR & EXTREME PRESSURE PROPERTIES

	20W 40
KINEMATIC VISCOSITY cst @ 100C	14.5-15.5
VISCOSITY INDEX, MIN	110
FLASH POINT, (COC) C, MIN	200
POUR POINT, C, MAX	-21
SULPHATED ASH, % WT, MAX	0.82
TBN, mgKOH/g, MIN	5.9

APPROVED BY:
M/s ESCORTS YAMAHA MOTOR LTD.
M/s ROYAL ENFIELD MOTORS
M/s BAJAJ AUTO

PRESS TO
RETURN



FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE