

HP Lubricants - Product Data Sheet RUST PREVENTIVES



HP RUSTOP 274, 276

PREMIUM QUALITY SOLVENT CUT BACK TYPE RUST PREVENTIVES USEFUL UNDER MODERATE TO EXTREME CONDITIONS CAPABLE RUST INHIBITION FOR EXTENDED PERIODS. THE PRODUCT CAN BE USED AFTER DILUTION OR AS SUPPLIED

APPLICATION AREAS:

THE PRODUCT IS WIDELY USED AS A FINAL RUST PREVENTIVE IN BALL BEARINGS AND FOR ALLOY STEELS. THE PRODUCT IS COMPATIBLE WITH LUBRICANTS. THE PRODUCT IS USED IN FINAL PACKING STAGE IN MANY CRITICAL APPLICATIONS. RUSTOP 276 IS CAPABLE OF RUST PREVENTION ON EVEN SEVERE SALTY AND HUMID ATMOSPHERES. THE PRODUCTS CAN BE APPLIED BY SPRAY OR SWABS.

PHYSIO CHEMICAL PROPERTIES:

PROPERTIES	HP RUSTOP	
	274	276
APPEARANCE	DULL	DULL
ACTION ON POLYETHYLENE BAG (SKF	NO ACTION	NO ACTION
METHOD)		
KINEMATIC VISCOSITY@ 40 deg C, cSt	18-28	20-30
NON VOLATILE % WT	19-24	45-50
COPPER STRIP CORROSION	1	1
AT 3Hrs. 100C, (ASTM), MAX		
WATER DISPLACEMENT TEST	PASS	PASS
FILM THICKNESS, MICRONS, MIN	8	8
FINGER PRINT NEUTRALISATION TEST	PASS	PASS

PERFORMANCE BENEFITS:

EASY APPLICATION
EASILY REMOVABLE BY SOLVENT
LUBRICANT COMPATIBLE
WIDE COVERAGE
SEVERE DUTY RUST PREVENTION

CONT...

FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST REGIONAL OFFICE