



HP Lubricants - Product Data Sheet



HP TRIMOFIN 20

NON STAINING TYPE STRAIGHT CUTTING OIL TREATED WITH CHLORINATED EP ADDITIVE. THIS OIL HAS LOW VISCOSITY AND IS LIGHT IN COLOUR.

APPLICATION AREAS :

PRODUCT IS RECOMMENDED FOR USE IN AUTOMOBILE, BEARING AND WATCH INDUSTRIES FOR HONING, LAPPING AND SUPER FINISHING OPERATIONS OF FERROUS AND NON-FERROUS METALS.

| PROPERTIES | HP TRIMOFIN 20 |
|--|-----------------------|
| KINEMATIC VISCOSITY @ 40 deg C,cSt | 4-8.4 |
| FLASH POINT deg C, COC, MIN | 110 |
| COPPER CORROSION 3HRS,@100 deg C, MAX | 1 |
| FOUR BALL OK LOAD, Kg, MIN | 240 |

PERFORMANCE BENEFITS :

EXCELLENT FINISH
EXCELLENT CHIP FLUSHING PROPERTIES
INCREASED TOOL LIFE

CONT...

FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE