



# HP Lubricants - Product Data Sheet



## HYLUBE X3 10W 30,40,50

- HYLUBE X3 10W 30,40,50 ARE MONOGRADE ENGINE OIL FOR SEVERE DUTY DIESEL ENGINE SERVICES
- MEETS API CD , US MILITARY MIL-L-45199B,E-DL2 OF IS:13656:1993 SPECIFICATION
- RECOMMENDED FOR USE IN ALLTYPES OF DIESEL ENGINES INCLUDING EARTH MOVING & CONSTRUCTION EQUIPMENTS . X3 10W GRADE CAN ALSO BE USED AS A HYDRAULIC FLUID .X3 40 GRADE HAS BEEN SPECIALLY DESIGNED FOR ENGINES OPERATING ON FUELS HAVING HIGHER SULPHUR CONTENT.
  - EXCELLENT THERMAL & OXIDATION STABILITY
  - EXCELLENT PERFORMANCE UNDER SEVERE CONDITIONS.

	10W	30	40	50
<b>KINEMATIC VISCOSITY cSt @ 40 deg C</b>	38	125	125	260
<b>KINEMATIC VISCOSITY cSt @ 100 deg C</b>	5	10-12	13-15	17-20
<b>VISCOSITY INDEX,MIN</b>	100	95	90	90
<b>FLASH POINT, (COC) C,MIN</b>	190	215	215	220
<b>POUR POINT, C , MAX</b>	-27	-6	-6	-6
<b>SULPHATED ASH,%WT,MAX</b>	1.3	1.3	2.0	1.3
<b>TBN ,mgKOH/g,MIN</b>	9	9	13	9

### APPROVED BY:

- M/s VST TILLERS
- M/s BEML
- M/s FUJI

PRESS TO  
RETURN



FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST  
REGIONAL OFFICE