

HP Lithon 2, 3, M2



LITHIUM SOAP MULTIPURPOSE GREASES. LITHON M2 CONTAINS MOLYBDENUM DISULPHIDE

MEETS SPECIFICATIONS:

IS:7623 GRADE 2 &3, IPSS 1-09-006

APPLICATION AREAS:

THE GREASES MEET THE REQUIREMENTS OF ALL INDUSTRIAL APPLICATIONS FOR PLAIN AND ANTIFRICTION BEARINGS. LITHON M2 IS SUITABLE FOR APPLICATIONS WHERE FRETTING CORROSION NEEDS TO BE AVOIDED (EXAMPLE: IN SPLINED SHAFTS)

PHYSIO CHEMICAL PROPERTIES:

PROPERTIES	LITHON 2	LITHON 3	LITHON M2
COLOUR	YELLOWISH	YELLOWISH	BLACK
NLGI NUMBER	2	3	2
WORKED	265-295	220-250	265-295
PENETRATION			
60X, @ 25 deg C			
DROP POINT,	180	180	180
deg C, MIN			
SOAP TYPE	LITHIUM	LITHIUM	LITHIUM

PERFORMANCE BENEFITS:

EXCELLENT WATER RESISTANCE
HIGH OXIDATION STABILITY
MAXIMUM STRUCTURAL STABILITY
SUPERIOR ANTI-RUST AND ANTI-CORROSION PROPERTIES

CONT...