



HP Lubricants - Product Data Sheet



HP PLUTEK 1, 2

EXTREME PRESSURE GREASES FOR HEAVY DUTY INDUSTRIAL APPLICATIONS DESIGNED FOR HEAVILY LOADED PLAIN AND ANTIFRICTION BEARINGS

**MEETS SPECIFICATIONS:
NLGI 1, 2 RESPECTIVELY**

APPLICATION AREAS :

FOR ALL PLAIN AND ANTIFRICTION HEAVILY LOADED BEARINGS OPERATING AT MODERATE SPEEDS OF 2000 RPM AND TEMPERATURES UPTO 70 DEG C

PHYSIO CHEMICAL PROPERTIES

PROPERTIES	PLUTEK 1	PLUTEK 2
COLOUR	BROWN	BROWN
NLGI NUMBER	1	2
WORKED PENETRATION 60 X, @25 deg C	310-340	265-295
DROP POINT,deg C, MIN	88	88
SOAP TYPE	CALCIUM	CALCIUM
TIMKEN OK LOAD lbs(Kg)	45(20.4)	45(20.4)
APPEARANCE	SMOOTH AND TACKY	SMOOTH AND TACKY

PERFORMANCE BENEFITS :

**EXCELLENT EP PROPERTIES
EXCELLENT ADHESION PROPERTIES
SUPERIOR WATER RESISTANCE**

CONT...

**FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE**