



HP Lubricants - Product Data Sheet



SPINTEK 5,12,15,22

SPINDLE OILS ARE LOW VISCOSITY LUBRICANTS MANUFACTURED FROM HIGHLY REFINED BASE STOCKS POSSESSING EXCELLENT CHEMICAL AND OXIDATION STABILITY AND FURTHER FORTIFIED WITH CAREFULLY SELECTED OXIDATION AND RUST INHIBITORS, ANTIWEAR AND ANTIFOAM AGENTS.

SPECIFICATIONS: IT MEETS IS : 493 (PART I) - 1993

APPLICATION AREAS :

THESE OILS ARE RECOMMENDED FOR LUBRICATION OF TEXTILE AND MACHINE TOOLS, SPINDLE BEARINGS, TIMING GEARS, CENTRIFUGAL SEPARATORS, POSITIVE DISPLACEMENT BLOWERS AND HYDRAULIC SYSTEM OF CERTAIN HIGH PRECISION MACHINE TOOLS.

SPINTEK GRADE ARE APPROVED BY MAJOR TEXTILE MACHINERY MANUFACTURES LIKE LMW, TEXTTOOL, TEXMACO ETC.

PROPERTIES	SPINTEK			
	5	12	15	22
VISCOSITY,CST.@40°C	9.5-13.4	9.0-11.0	14-16	20-24
VISCOSITY,INDEX MIN	90	90	90	90
FLASH POINT, (COC), °C, MIN	150	150	166	172
POUR POINT, °C, MAX	(-) 6	(-) 6	(-) 3	(-) 3
TOTAL ACIDITY,mg KOH/gm	1.5	1.5	1.5	2.0

PERFORMANCE BENEFITS:

SPINTEK OILS HAVE FOLLOWING OUTSTANDING CHARACTERISTICS.

- GOOD STRENGTH OF OIL FILM
- GOOD DEMULSIBILITY
- HIGH CHEMICAL STABILITY
- LOWEST FLUID FRICTION
- RESISTANCE TO RUSTING AND CORROSION

CONT...

FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST REGIONAL OFFICE