



# HP Lubricants - Product Data Sheet



## NON-SOAP GREASES

### TISON 2

A CLAY THICKENED GREASE HAVING GOOD OXIDATION RESISTANCE AND THERMAL STABILITY FOR USE IN BOTH PLAIN AND ANTI-FRICTION BEARINGS. IT CAN LUBRICATE SATISFACTORILY AT TEMPERATURE UP TO 230°C AND WILL NOT MELT OR SOFTEN APPRECIABLY EVEN AT HIGHER TEMPERATURE.

### TISONA M2

A CLAY THICKENED GREASE WITH MOLYBDENUM DISULPHIDE ADDED TO IT TO REDUCE FRICTION AT HIGH TEMPERATURES. FURTHER FORTIFIED WITH ANTI-OXIDATION, ANTI-CORROSION AND ANTIWEAR ADDITIVES.

TISONAM M2 MEETS IS : 12790-1989 GRADE 3 AND IPSS : 1-09-008

PROPERTIES	TISONA	
	2	M2
<b>COLOUR</b>	<b>BROWN</b>	<b>BLACK</b>
<b>WORKED PENETRATION AT 25°C</b>	<b>260/290</b>	<b>280/310</b>
<b>DROP POINT, °C, MIN</b>	<b>250</b>	<b>280</b>

THESE ARE RECOMMENDED FOR THE LUBRICATION OF MACHINE ELEMENTS, PLAIN BEARINGS, ANTI-FRICTION BEARINGS OPERATING AT HIGH TEMPERATURE.

PRESS TO  
RETURN



FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST  
REGIONAL OFFICE